Printing date 11/11/2016 Revised On 11/11/2016

1 Identification of the substance and manufacturer

Trade name: STRIPE WHITE INVERTED TIP

0000160652 Product code:

Product category PC9a Paints and coatings. Manufacturer/Supplier: Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 phone: 815-895-9101

www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking. **Precautionary statements**

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use

Use only outdoors or in a well-ventilated area.

Do not breathe dust/fume/gas/mist/vapors/spray. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

| Dangerous components: | | |
|-----------------------|-------------------|--------|
| | propane | 17.63% |
| 1317-65-3 | Calcium Carbonate | 14.79% |
| 64742-89-8 | VM&P Naphtha | 14.07% |
| 106-97-8 | | 10.36% |
| | titanium dioxide | 6.1% |
| 64742-47-8 | Mineral Spirits | 5.17% |

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact: After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 2)

Printing date 11/11/2016 Revised On 11/11/2016

Trade name: STRIPE WHITE INVERTED TIP

Methods and material for containment and cleaning up: Ensure adequate ventilation. (Contd. of page 1)

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (United States GHS) Long-term value: 1800 mg/m³, 1000 ppm REL (United States GHS) Long-term value: 1800 mg/m³, 1000 ppm TLV (United States GHS) refer to Appendix F inTLVs&BEIs book; NIC-EX

106-97-8 n-butane

REL (United States GHS) Long-term value: 1900 mg/m³, 800 ppm Short-term value: (2370) mg/m³, (1000) ppm NIC-EX TLV (United States GHS)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. **Breathing equipment:**

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined.

pH-value: Not determined. Melting point/Melting range Undetermined. -44 °C (-47 °F) **Boiling point:** Flash point: -19 °C (-2 °F) Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % **Upper Explosion Limit:** 10.9 Vol % Not determined. Vapor pressure:

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Not determined. Vapor density Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Viscosity: Not determined. **VOC content (less exempt solvents):** 48.7 %

Water: 22.0 % Solids content: 28.2 %

10 Stability and reactivity

Chemical stability:

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Not fully evaluated.

Possibility of hazardous reactions:

No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

(Contd. on page 3)

Printing date 11/11/2016 Revised On 11/11/2016

Trade name: STRIPE WHITE INVERTED TIP

13463-67-7 titanium dioxide

(Contd. of page 2)

>20000 mg/kg (rat) LD50 Oral Dermal LD50 >10000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide

2B

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A UN1950

Consumer Commodity ORM-D AEROSOLS, flammable DOT

ADR 1950 AEROSOLS

Transport hazard class(es):

Marine pollutant: No

Warning: Gases F-D,S-U Special precautions for user:

EMS Number:

Packaging Group: UN "Model Regulation":

UN1950, AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL

PROTECTION ACT:

WHMIS Symbols for Canada:

None of the ingredients is listed.

All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

A - Compressed gas

EPA:

16 Other information

Contact: Regulatory Affairs 11/11/2016 / -Date of preparation / last revision