

## Klean Strip Odorless Mineral Spirits

Revision: 11/05/2021

Supersedes Revision: 08/05/2020

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	Klean Strip Odorless Mineral Spirits	
<b>Company Name:</b>	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100
<b>Web site address:</b>	www.wmbarr.com	
<b>Emergency Contact:</b>	3E 24 Hour Emergency Contact	(800)451-8346
<b>Information:</b>	W.M. Barr Customer Service	(800)398-3892
<b>Intended Use:</b>	Paint, stain, and varnish thinning.	
<b>Product Code:</b>	GKSP94006P, QKSP94005, QKSP945, GKSP94006, GKSP94214	

## 2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 3

Skin Corrosion/Irritation, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

Aspiration Toxicity, Category 1

**GHS Signal Word:****Danger****GHS Hazard Phrases:**

Flammable liquid and vapor.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause drowsiness or dizziness.

**GHS Precautionary Phrases:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing gas/mist/vapors/spray.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Keep cool.

**GHS Response Phrases:**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
IF ON SKIN: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Call a POISON CENTER or doctor/physician if you feel unwell.  
Specific treatment see label.  
Do NOT induce vomiting.  
If skin irritation occurs, get medical advice/attention.  
Take off contaminated clothing and wash before re-use.

**GHS Storage and Disposal Phrases:**

Store container tightly closed in well-ventilated place.  
Store locked up.  
Dispose of contents/container according to local, state and federal regulations.

## Klean Strip Odorless Mineral Spirits

Revision: 11/05/2021

Supersedes Revision: 08/05/2020

<b>OSHA Regulatory Status:</b>	This material is classified as hazardous under OSHA regulations.
<b>Potential Health Effects (Acute and Chronic):</b>	Acute health effects
	Eye contact: No known significant effects or critical hazards.
	Inhalation: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
	Skin contact: Causes skin irritation. Defatting to the skin.
	Ingestion: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

**Medical Conditions Generally** None known.

**Aggravated By Exposure:**

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	100.0 %

### 4. FIRST AID MEASURES

<b>Emergency and First Aid Procedures:</b>	<p>Inhalation: If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.</p> <p>Skin contact: Wash with soap and large quantities of water for at least 15 minutes. Seek medical attention if irritation from contact persists.</p> <p>Eye contact: Immediately flush eyes with water, remove any contact lens, continue flushing with water for at least 15 minutes. Get medical attention.</p> <p>Ingestion: Do not induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.</p>
<b>Signs and Symptoms Of Exposure:</b>	Primary routes of exposure: Inhalation, ingestion, and dermal.
<b>Note to Physician:</b>	Call your local poison control center for further instructions.

## Klean Strip Odorless Mineral Spirits

Revision: 11/05/2021

Supersedes Revision: 08/05/2020

## 5. FIRE FIGHTING MEASURES

<b>Flammability Classification:</b>	NFPA Class II
<b>Flash Pt:</b>	> 105.80 F Method Used: TAG Closed Cup
<b>Explosive Limits:</b>	LEL: .6 UEL: 5.5
<b>Autoignition Pt:</b>	456.80 F
<b>Suitable Extinguishing Media:</b>	Use carbon dioxide, dry chemical powder, or foam.
<b>Fire Fighting Instructions:</b>	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
<b>Flammable Properties and Hazards:</b>	No data available.
<b>Hazardous Combustion</b>	No data available.
<b>Products:</b>	

## 6. ACCIDENTAL RELEASE MEASURES

<b>Steps To Be Taken In Case Material Is Released Or Spilled:</b>	<p>Clean-up: Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep flares, smoking or flames out of hazard area.</p> <p>Small spills: Take up the spilled liquid with sand, earth, or other noncombustible absorbent material and place in a plastic container where applicable.</p> <p>Large spills: Dike far ahead of spill for later disposal.</p>
---	---

## 7. HANDLING AND STORAGE

<b>Precautions To Be Taken in Handling:</b>	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.
<b>Precautions To Be Taken in Storing:</b>	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	ACGIH TLV	TLV: 200 mg/m3	

## Klean Strip Odorless Mineral Spirits

Revision: 11/05/2021

Supersedes Revision: 08/05/2020

<b>Respiratory Equipment (Specify Type):</b>	For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.
<b>Eye Protection:</b>	Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.
<b>Protective Gloves:</b>	Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.
<b>Other Protective Clothing:</b>	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.
<b>Engineering Controls (Ventilation etc.):</b>	Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.
<b>Work/Hygienic/Maintenance Practices:</b>	A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ ] Gas [X] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Colorless to light yellow Solvent odor Odor threshold not determined.
<b>pH:</b>	ND
<b>Melting Point:</b>	-72.40 F
<b>Boiling Point:</b>	318.20 F - 354.20 F
<b>Flash Pt:</b>	> 105.80 F Method Used: TAG Closed Cup
<b>Evaporation Rate:</b>	< 1 (BuAC=1)
<b>Flammability (solid, gas):</b>	No data available.
<b>Explosive Limits:</b>	LEL: .6 UEL: 5.5
<b>Vapor Pressure (vs. Air or mm Hg):</b>	3 MM HG at 25.0 C
<b>Vapor Density (vs. Air = 1):</b>	4.5 Air = 1
<b>Specific Gravity (Water = 1):</b>	0.78
<b>Density:</b>	6.5
<b>Solubility in Water:</b>	Slight
<b>Solubility Notes:</b>	Very slightly soluble in the following materials: cold water. (1.5 g/l)
<b>Saturated Vapor Concentration:</b>	ND

# SAFETY DATA SHEET

## Klean Strip Odorless Mineral Spirits

<b>Octanol/Water Partition Coefficient:</b>	ND
<b>Percent Volatile:</b>	100.0 % by weight.
<b>VOC / Volume:</b>	780.0000 G/L
<b>Autoignition Pt:</b>	456.80 F
<b>Decomposition Temperature:</b>	No data.
<b>Viscosity:</b>	ND
<b>Additional Physical Information</b>	Conductivity = <5 picosiemens/meter (unadditized) ND = Not Determined

### 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ]    Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. Do not store with strong oxidizing agents.
<b>Incompatibility - Materials To Avoid:</b>	Incompatible with strong oxidizing agents.
<b>Hazardous Decomposition or Byproducts:</b>	Thermal decomposition may produce carbon monoxide and carbon dioxide.
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ]    Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.

### 11. TOXICOLOGICAL INFORMATION

<b>Toxicological Information:</b>	In animal studies utilizing mineral spirits containing up to 22% aromatics indicated that the acute central nervous system effects are reversible. Based on existing animal studies, the potential for persistent effects is not clear.
<b>Irritation or Corrosion:</b>	Primary dermal irritation studies (four hour exposure) in rabbits utilizing mineral spirits containing less than 2% aromatics resulted in slight to moderate skin irritation. In humans, mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented.  Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations. Also, sensory respiratory tract irritation was evident by reduced breathing rates in the test animals in certain studies.
<b>Symptoms related to Toxicological Characteristics:</b>	Eye contact: Adverse symptoms may include the following: pain or irritation watering redness  Inhalation: Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination. Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness  Skin contact: Adverse symptoms may include the following: irritation redness dryness cracking  Ingestion: Adverse symptoms may include the following: nausea or vomiting

# SAFETY DATA SHEET

## Klean Strip Odorless Mineral Spirits

**Carcinogenicity/Other Information:** ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	n.a.	n.a.	A4	n.a.

### 12. ECOLOGICAL INFORMATION

**General Ecological Information:** This product has not been tested as a whole. Information below will be for individual ingredients.

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose in accordance with applicable local, state, and federal regulations.

### 14. TRANSPORT INFORMATION

#### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Paint related material  
**DOT Hazard Class:** 3 FLAMMABLE LIQUID  
**UN/NA Number:** UN1263 **Packing Group:** III



**Additional Transport Information:** The shipper may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### 15. REGULATORY INFORMATION

#### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	TSCA: Inventory

**Additional Regulatory Information:** This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

**SAFETY DATA SHEET**  
**Klean Strip Odorless Mineral Spirits**

Revision: 11/05/2021  
Supersedes Revision: 08/05/2020

**16. OTHER INFORMATION**

<b>Revision Date:</b>	11/05/2021	<b>Previous revision:</b>	08/05/2020
<b>Preparer Name:</b>	W.M. Barr EHS Department (901)775-0100		

**Additional Information About This Product:** No data available.

**Company Policy or Disclaimer:** The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.