

Revision Number: 004.0 Issue date: 03/09/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE SI 587 BL AE known as 587 IDH number: 743517

Blue RTV 190ml AE

 Product type:
 Silicone sealant
 Item number:
 40462

 Restriction of Use:
 None identified
 Region:
 United States

Company address: Contact information:
Henkel Corporation Telephone: (860) 571-5100

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CONTENTS UNDER PRESSURE.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HARMFUL IF INHALED.CONTAINS GAS UNDER PRESSURE: MAY EXPLODE

IF HEATED.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	4
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
GASES UNDER PRESSURE	Liquef. Gas





Precautionary Statements

Prevention: Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated

work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear

protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get

medical attention. Take off contaminated clothing.

Storage:

Protect from sunlight. Store in a well-ventilated place.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

IDH number: 743517 Product name: LOCTITE SI 587 BL AE known as 587 Blue RTV 190ml AE Page 1 of 6

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Reinforcing Filler	Proprietary	30 - 60	
Silicone Resin	Proprietary	10 - 30	
Norflurane	811-97-2	5 - 10	
Oximino silane	Proprietary	1 - 5	
Aluminum	7429-90-5	0.1 - 1	
Reactive Silane	Proprietary	0.1 - 1	

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Wipe off paste with paper towel or cloth. Wash with soap and water. If skin

irritation persists, call a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. If eye irritation persists, consult a specialist.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Keep individual calm. Get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Use water spray to keep fire exposed containers cool and disperse vapors.

Unusual fire or explosion hazards: Contents under pressure. Closed containers may rupture (due to build up of

pressure) when exposed to extreme heat.

Hazardous combustion products: Formaldehyde. Silica fume.

IDH number: 743517

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Maintain good ventilation for large spills. Spilled material will solidify. Scrape

up as much material as possible. Place scrap material in a well ventilated area

and allow to cure to rubber.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and

cause eye irritation.

Storage: For safe storage, store at or below 32 °C (89.6 °F)

Keep container closed.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Reinforcing Filler	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Silicone Resin	None	None	None	None
Norflurane	None	None	1,000 ppm (4,240 mg/m3) TWA	None
Oximino silane	None	None	None	None
Aluminum	1 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL (as AI) Respirable dust. 15 mg/m3 PEL (as AI) Total dust. None		None
Reactive Silane	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: Blue

Odor: mild, Petroleum
Odor threshold: Not available.
pH: Not available.

Vapor pressure: < 5 mm hg (20 °C (68°F))

Boiling point/range:

Melting point/ range:

Specific gravity:

Vapor density:

Not available.

1.31 at 20 °C (68°F)

Not available.

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: Not available.
Evaporation rate: Not available.

Solubility in water: Polymerises in presence of water.

Partition coefficient (n-octanol/water): Not available. VOC content: 3.9 %; 50.7 g/l

IDH number: 743517

Product name: LOCTITE SI 587 BL AE known as 587 Blue RTV 190ml AE Page 3 of 6

Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 743517

Methyl ethyl ketoxime formed during cure. Oxides of carbon. Oxides of silicon. Formaldehyde

Incompatible materials: Polymerizes on contact with water. Acids and bases. Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Moisture.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Harmful if inhaled.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: Not expected under normal conditions of use. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Reinforcing Filler	None	Nuisance dust
Silicone Resin	None	Irritant
Norflurane	None	Cardiac, Central nervous system, Irritant, Respiratory, Skin
Oximino silane	None	Irritant, Allergen
Aluminum	None	Central nervous system, Irritant, Lung
Reactive Silane	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Reinforcing Filler	No	No	No
Silicone Resin	No	No	No
Norflurane	No	No	No
Oximino silane	No	No	No
Aluminum	No	No	No
Reactive Silane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Cured

rubber can be incinerated or landfilled following EPA and local regulations.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, non-flammable

Hazard class or division: 2.2 Identification number: UN 1950 Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

AEROSOLS
2.2
UN 1950
None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 743517

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

Issue date: 03/09/2015

Product name: LOCTITE SI 587 BL AE known as 587 Blue RTV 190ml AE Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 743517