SAFETY DATA SHEET

1. Identification

Product identifier Heavy Duty Clear Penetrating Grease

Other means of identification

03056 Product code

Recommended use Penetrating grease **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries, Inc. Company name **Address** 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

800-272-4620 **Customer Service** 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

> Gases under pressure Liquefied gas

Health hazards Serious eye damage/eye irritation Category 2B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes eye

irritation. May cause drowsiness or dizziness.

Precautionary statement Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Wash hands thoroughly after handling.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical attention.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

Not applicable.

Material name: Heavy Duty Clear Penetrating Grease

3. Composition/information on ingredients

Chemical name	Common name and synonyms	CAS number	%
Heptane, branched, cyclic and linear		426260-76-6	20 - 30
Liquefied Petroleum Gas		68476-85-7	20 - 30
Polybutene		9003-29-6	20 - 30
Distillates (petroleum), hydrotreated light		64742-47-8	5 - 10
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	5 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Mixturoo

InhalationRemove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. Call a POISON CENTER or doctor/physician.

Skin contactWash off with soap and water. Get medical attention if irritation develops and persists. Take off contaminated clothing and wash before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Do not induce vomiting.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting.

Most important Exposed individuals may experience eye tearing redness, and discomfort. Vapors have

Most important Exposed individuals may experience eye tearing, redness, and discomfort. Vapors have a narcotic effects, acute and delayed Exposed individuals may experience eye tearing, redness, and discomfort. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause drowsiness or dizziness.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

the chemical

Suitable extinguishing media Foam. Dry chemicals. Carbon dioxide (CO2).

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

media

Specific hazards arising from Contents under pressure. Pressurized container may explode when exposed to heat or flame. This

product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants.

Material will float and may ignite on surface of water.

Special protective equipment Wear self-contained breathing apparatus and protective clothing. and precautions for firefighters

Fire-fighting
equipment/instructions
In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Avoid breathing gas. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Dike far ahead of spill for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with skin and eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure controls/personal protection

Components	Туре	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
•		2000 mg/m3	
		500 ppm	
Liquefied Petroleum Gas CAS 68476-85-7)	PEL	1800 mg/m3	
,		1000 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
JS. NIOSH: Pocket Guide to Chemical	Hazards		
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
iquefied Petroleum Gas CAS 68476-85-7)	TWA	1800 mg/m3	
,		1000 ppm	

Biological limit values Appropriate engineering

No biological exposure limits noted for the ingredient(s).

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene.Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to Respiratory protection

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Aerosol.

Color Clear, Colorless, Characteristic. Odor **Odor threshold** Not available Not available. Ha Not available Melting point/freezing point Initial boiling point and boiling 175 °F (79.4 °C)

range

< 20 °F (< -6.7 °C) Tag Closed Cup Flash point

Evaporation rate Fast.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits 0.5 % estimated Flammability limit - lower

Flammability limit - upper

(%)

6.7 % estimated

Vapor pressure

2343.9 hPa estimated

Vapor density > 1 (air = 1)

0.72 Relative density Solubility (water) Negligible. Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature

410 °F (210 °C) estimated

Decomposition temperature Not available. Viscosity (kinematic) Not available Percent volatile 78 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Strong oxidizing agents. Amines. Chlorine. Nitric plus acetic acids. Nitric plus sulfuric acids. Incompatible materials

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Prolonged inhalation may be harmful. Prolonged or excessive inhalation may cause respiratory

tract irritation.

Skin contact Prolonged contact may cause irritation and defatting of skin.

Eye contact Causes eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Exposed individuals may experience eye tearing, redness, and discomfort. Symptoms of

overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity Narcotic effects. Causes eye irritation.

Product Species **Test Results** Heavy Duty Clear Penetrating Grease Acute Dermal LD50 Rabbit 9090.9092 mg/kg estimated Inhalation LC50 Rat 17500 ppm, 4 hours estimated 53.4247 mg/l, 4 hours estimated Oral

Rat

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

LD50

Causes eye irritation.

irritation

Not available. Respiratory sensitization

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard If aspirated (liquid enters the lungs), it may be rapidly absorbed through the lungs and result in

injury to other body systems. May also cause gastro-intestinal distress.

Prolonged inhalation may be harmful. Repeated and prolonged overexposure to solvents may lead **Chronic effects**

to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness, and loss of coordination are signs that solvent levels are too high. Intentional misuse by

13931.3896 mg/kg estimated

deliberately concentrating and inhaling the contents may be harmful or fatal.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the
	possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
Heavy Duty Clear Pen	etrating Grease		
Acute			
Crustacea	EC50	Daphnia	5000 mg/l, 48 hours estimated
Fish	LC50	Fish	3452.6113 mg/l, 96 hours estimated
Components		Species	Test Results

Acute

EC50 Invertebrate (saltwater) 4720 mg/l, 96 hours

Aquatic

Acute

Fish LC50 Bluegill (Lepomis macrochirus) 1740 mg/l, 96 hours

Fathead minnow (Pimephales promelas) 45 mg/l, 96 hours

Polybutene (CAS 9003-29-6)

Acute

Crustacea EC50 Daphnia > 1000 mg/l, 48 hours

> 1000 mg/l, 96 hours (similar material) Fish LC50 Fish

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Contents under

pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into

sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations. Empty container can be recycled.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions 306 None Packaging non bulk Packaging bulk None

IATA

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

2.1 Class Subsidiary risk

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN1950 **UN** number

UN proper shipping name Transport hazard class(es) AEROSOLS, LIMITED QUANTITY

2 Class Subsidiary risk

Packing group Not applicable.

Environmental hazards

Marine pollutant Nο

Not available. **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: Heavy Duty Clear Penetrating Grease 897 Version #: 01 Issue date: 01-14-2014

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. New Jersey RTK - Substances: Listed substance

Liquefied Petroleum Gas (CAS 68476-85-7)

US. Massachusetts RTK - Substance List

Liquefied Petroleum Gas (CAS 68476-85-7)

US. Pennsylvania RTK - Hazardous Substances

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Liquefied Petroleum Gas (CAS 68476-85-7)

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 73 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products This product is regulated as a Penetrant. This product is not compliant to be sold for use in

California. This product is compliant in all other states.

 VOC content (CA)
 45 %

 VOC content (OTC)
 45 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-14-2014 **Prepared by** Allison Cho

Version # 01

Further information Not available.

HMIS® ratings Health: 2
Flammability: 4

Physical hazard: 0
Personal protection: B

NFPA ratings Health: 2

Flammability: 4 Instability: 0

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries.

Material name: Heavy Duty Clear Penetrating Grease